

Page No: 3
Revision: 7
Issue Date: 03/01/20

SECTION: A 0055 – AIRFRAME INSPECTION PROGRAM
TYPE: 300 HOUR / 12 MONTH INSPECTION
NOTE:

MAINTENANCE ACTION		REFERENCE	MECHANIC'S INITIALS
7.5	Verify operation of ENGINE OUT and LOW ROTOR RPM audio and mute switch (if installed).		
7.6	Verify illumination of all caution panel annunciator light segments by depressing test switch, or each individual light segment, as applicable.		
7.7	Verify instrument lighting and dimming capabilities.		
A 0055.8 POST INSPECTION			
8.1	Ensure applicable servicing requirements have been carried out.	Chapter 12	
8.2	Check oil level of transmission, hydraulic tank, engine and tail rotor gearbox prior to running helicopter.		
8.3	Complete a ground run at 100% NR to check for leaks and confirm system operation and parameters are within Flight Manual limitations. – Qualified pilot only.	BHT-206L-FM-1	
8.4	Check the voltage regulator setting. Adjust as required.	Chapter 96	
8.5	Replace or close all applicable trim panels, covers, access and inspection doors/covers as necessary.		
8.6	Perform Functional Check Flight if required per Bell 206L Maintenance Manual or RFM as appropriate.		
8.7	Make an entry in the appropriate logbook (refer to the following page for wording of approval for return to service).		