

Page No: 1
Revision: 4
Issue Date: 04/30/16

SECTION: A 0350 – AIRFRAME INSPECTION PROGRAM
TYPE: 300 HOUR / 12 MONTH HYDRAULIC SYSTEM SERVICING
NOTE:

Registration No.: N Start Aircraft Start Total Time: _____
Aircraft S/N: _____ Date: _____ Aircraft Start Total Cycles: _____

Reference: BHT 206L MM-1 Chapter 12

MAINTENANCE ACTION		REFERENCE	MECHANIC'S INITIALS
A 0350.1 GENERAL			
1.1	Logbook review for recorded discrepancies. Correct discrepancies on installed equipment.		
1.2	Ensure all applicable and required Special Inspections, Alert Service Bulletins (ASB's), Engine Service Bulletins, and Airworthiness Directives (AD's) are accomplished.		
1.3	Replace all life limited components that have completed published operating limits.	Bell 206L MP	
1.4	Overhaul all components that have completed published operating limits.	Bell 206L MP	
A 0350.2 HYDRAULIC			
2.1	Drain hydraulic fluid	Chapter 29	
2.2	Clean out bottom of hydraulic reservoir.		
2.3	Remove and inspect hydraulic filter bowls and elements.		
2.4	Clean hydraulic filter elements. Note: Filters may only be cleaned a maximum of three (3) times. CAUTION Do not put the filter elements into an ultrasonic cleaner. This will damage the element.		
2.5	Install new filter(s) if needed. (N/A if not needed)		
2.6	Reinstall filter assembly and service hydraulic system.		
A 0350.3 POST INSPECTION			
3.1	Complete a ground run at 100% NR to check for leaks and confirm system operation.	BHT-206L-FM-1	
3.2	Replace or close all applicable trim panels, covers, access and inspection doors/covers as necessary.		
3.3	Perform Functional Check Flight if required per Bell 206L Maintenance Manual or RFM as appropriate.		
3.4	Make an entry in the appropriate logbook (refer to the following page for wording of approval for return to service).		

Page No: 2
Revision: Orig
Issue Date: 05/01/14

SECTION: A 0350 – AIRFRAME INSPECTION PROGRAM
TYPE: 300 HOUR / 12 MONTH HYDRAULIC SYSTEM SERVICING
NOTE:

Upon satisfactory completion of each inspection item, the mechanic shall initial the pertinent space as provided. All mechanics shall sign and initial, in the space provided, at the end of the form.

At the completion of each inspection form, an A&P mechanic shall check the entire form for completion and then enter his/her signature, certificate type and number, and date in the space provided at the end of the form. The same individual is also responsible for making the logbook entry shown at the conclusion of this inspection.

I certify that I have inspected and/or completed all the items initialed by me in accordance with Maritime Helicopters' Bell 206L Series Approved Aircraft Inspection Program and found them to be in an airworthy condition except as may be noted in the Aircraft Logbook.

<u>INITIALS</u>	<u>SIGNATURE</u>	<u>CERTIFICATE TYPE & NUMBER</u>

I have reviewed this inspection form to verify that all items have been completed and have made an entry in the Aircraft Log Book.

I certify that this aircraft has been inspected in accordance with Maritime Helicopters' Bell 206L Series AAIP – A 0350 – 300 Hour 12 Month Hydraulic System servicing and was determined to be in an airworthy condition.

Registration No.: N End Aircraft Ending Total Time: _____
Aircraft S/N: _____ Date: _____ Aircraft Ending Total Cycles: _____

Signature: _____ Certificate Type & No: _____