

MARITIME HELICOPTERS				MINIMUM EQUIPMENT LIST			
AIRCRAFT: Piper PA-32 SERIES				REV: ORIGINAL DATE: 12/31/2021		PAGE NO. 34-1	
JASC SYSTEM & TITLE		1. REPAIR CATEGORY					
JASC CODE & ITEM NO.	COMPONENT DESCRIPTION		2. NUMBER INSTALLED				
				3. NUMBER REQUIRED FOR DISPATCH			
					4. REMARKS & EXCEPTIONS		
34. NAVIGATION							
3400-01	VHF Navigation Systems						
-01	VOR	C	1	0	May be inoperative provided navigation is not predicated on its use.		
-02	ILS						
-01	Localizer	C	1	0	Aircraft shall be operated VFR only.		
-02	Glideslope	C	1	0	Aircraft shall be operated VFR only.		
3416-02	Altimeter	C	2	1	Right side may be inoperative provided operations do not require a second in command.		
3434-01	Marker Beacon	C	1	0	May be inoperative provided Marker Beach is not required for planned approach.		
3450-01	Automatic Dependent Surveillance-Broadcast (ADS-B) System (In and Out)	B	1	0	May be inoperative provided prior to flight, authorization is obtained from ATC facilities having jurisdiction over the planned route of flight using an approved authorization process. NOTE: Any ADS-B In function that operates normally may be used. (O) For operation with an inoperative ADS-B Out, the pilot shall proceed to the airport of ultimate destination, including any intermediate stops, or to proceed to a place where suitable repairs can be made or both. The deviation request may be made at any time.		
		D	1	0	May be inoperative for operations outside of Class B and Class C airspace, all airspace within 30nm of an airport listed in Appendix D, Section 1, of Part 91 and all airspace above the ceiling and within the lateral boundaries of a Class B or C airspace designated for an airport upward to 10,000 feet MSL. NOTE: Any ADS-B function that operates normally may be used.		